

SYSTEMS

SSR

SHORT SCROLL RACK





# EASE OF INSTALLATION AND SERVICE



*Sealed stubs.*



*Full service access front and rear.*



All Tyler systems are built to rigid quality-control standards to ensure long-life dependability. We only use the highest-grade materials to meet local noise ordinances and environmental regulations. By eliminating the need for machine rooms and mechanical centers, the SSR eliminates the need for expensive steel reinforcements and large concrete curbs required with large mechanical centers.

## Features

- Sealed stubs.
- Full-service access, front and rear.
- Easily removable panels.
- Soundproofing insulation.

We took the industry-leading features of Tyler's quality parallel rack products and packed them into a compact package. As a result, SSR offers all the performance of full-size refrigeration racks in a fraction of the space.

## SSR Models and Dimensions

SSR Rack Designation	6 HP ZF18 and Smaller		7½ HP ZF24 and Larger	Maximum Number of Circuits	Overall Length	Overall Height	Overall Depth
SSR-S03R/B	0	AND	3	9	123	45	45
SSR-S40R/B	4	AND	0	9	123	45	45
SSR-M04R/B	0	AND	4	12	140	45	45
SSR-M50R/B	5	AND	0	12	140	45	45
SSR-M41R/B	4	AND	1	12	140	45	45
SSR-L05R/B	0	AND	5	15	157	45	45
SSR-L60R/B	6	AND	0	15	157	45	45
SSR-L51R/B	5	AND	1	15	157	45	45
SSR-L420R/B	4	AND	2	15	157	45	45

# SSR

## SHORT SCROLL RACK



### Standard Features

- Specially designed for scroll compressors
- Industry standard controls (CPC, Com-Trol, Danfoss, Novar, Encore, ECI, and more).
- Discrete station EPR piping, full-size receivers, and easy-access panels are standard.
- One rack can be applied to low- or medium-temp applications, up to 75HP per system.
- Designed for R-22, R-404A, or R-507.
- Insulated panels reduce noise transmitted to the environment.
- UL-listed.
- Front-mounted compressors for easy service and replacement.
- Forced ventilation of control panel.

### In-Store Benefits

- Individual breakers and contactors to protect compressors.
- Remote solid-state refrigeration controls can be mounted on coolers or back walls for easy communication to rooftop equipment.
- Substantial refrigerant reductions and close-to-the-fixture installation reduce cost.
- Easily removable panels, simple one-man service reduces service costs.
- Factory-mounted full-size drier protects system.
- Stations located at the SSR, not on the sales floor.

### Performance Options

- Split suction
- Gas or electric defrost
- Mechanical subcooling
- Integral air-cooled condenser
- Heat reclaim
- Custom roof curb
- Enviroguard™ controls
- Floor mounting stand
- Piping chase in the base or in the back of unit.
- 208, 380, 460, and 575v;  
50 or 60 Hz

www.tylerrefrigeration.com  
e-mail sales@tylerrefrigeration.com  
1-800-845-0821

A member of the United Technologies Corporation family.  
Stock symbol UTX.



TY 825 03/01  
Printed in USA